# RD1100™ & RD1500™ Ground Penetrating Radar

Complete range of utility-locating radars



# Radiodetection's RD1100 & RD1500 Ground Penetrating Radar


Innovative tools for finding buried utilities



RD1100 provides locate professionals, surveyors and other users with the tool they need to trace and mark the position of all types of cable and pipe, including plastic and ceramic. Built in as standard is the ability to take Screenshots which are saved to internal memory for immediate emailing via Wi-Fi or later export to USB memory stick. GPS positioning is captured for integration into Google Earth™.


**RD1500** takes utility locating to the next level, offering users easily interpreted Depth Slices as well as traditional Line Views.

Use proprietary **FrequenSee™** technology to highlight small/shallow, medium or large/deep buried utilities. Enhance the RD1500 with software to export GPR data and perform detailed analysis, and with external GPS for higher positional accuracy.




Geo-referenced data


Display the position of your surveys in Google Earth™ and other geo-referencing programs.



Screen captures
Add markers via the touch
screen display to highlight
features of interest.



Depth Slices (RD1500)
View horizontal slices at
different depths to display
cables, pipes and other utilities
in unprecedented clarity.



On-site Map View (RD1500) View your identified features in plan map view using the optional external GPS.

# Advanced Reporting with RD1500 data analysis PC software

RD1500's Enhancement Package includes the comprehensive EKKO\_Project PC software solution for GPR data analysis and management, allowing you to:

- Slice through the depth data on your computer
- Generate PDF reports that include data images, screenshots and photos alongside your text and company logo
- Export data to other formats like CSV, SEG-Y etc.

3 additional modules to add to the Enhancement Package, for even greater levels of analysis, are available in Utility Suite:

- LineView modifies and displays GPR lines
- SliceView processes and displays grid data, and can output data for 3D visualization and geo-referencing software programs
- Interpretation for adding point, polyline, box and annotation interpretations to GPR lines in post-processing

#### Table of specifications

	RD1100 & RD1500	Options & comments
Sensor frequency	250MHz Ultra Wide Band	RD1500: Includes Frequen <i>See</i>
Signal Enhancement	DynaQ (optimizes data quality with cart speed). Spatial filtering.	
Data Analysis	In field analysis	RD1500: Post- processing analysis with EKKO_Project and Utility Suite (option)
Touch Screen Display	Size: 21cm (8") diagonal	Enhanced: Upgraded Display Unit package
Power	Consumption: 1.25A at 12V Battery: 12V, 9Ah Lead Acid	Battery life typically 4-6hrs
Spatial interval	5 cm (2")	
Depth range	Up to 8m (27') maximum	Ground conditions dependent
Display depth scale	1m-8m (3'-30')	
Languages supported	Non-lingual icons, English, Spanish, French, German	
Dimensions (H x W x D)	100 x 70 x 115cm (39.4 x 27.6 x 45.3")	
Weight	22 kg (48lb)	
Operating temperature range	Display: -10° to +50°C (14°F to +122°F) Sensor: -40°C to +50°C (-40°F to 122°F)	
Environmental protection	IP65	
Compliance	CE, FCC, ETSI, Industry Canada	
Standard warranty	1 year	






#### Instant email

Generate and deliver mini reports from your survey site by connecting to a Wi-Fi network or by using your phone as a hotspot. Instant information, higher productivity.


# RD1500<sub>Mini Report</sub>

Project	3	
Screen Capture Number	14	
Date Collected	April 7 2016 10:51 AM	
Mode	Slice View	
Grid	Grid02	
Grid Size	5 x 5 m	
Grid Resolution	Low (1.0 m)	
Soil Cal	Dry Soil (120)	
Slice Depth	0.4-0.5 m	
Slice Color Palette (Contrast)	2 (Medium)	
Grid Line Visibility	Partial	
Selected Line	LineY0	
Depth	3.0 m	
Line Color Palette	7	
Filter	ON	
Gain Level	3	
DynaT	All	



# RD1100 Mini Report

Screen Capture Number	5
Date Collected	April 5 2016 10:14 AM
Mode	Line Scan
Depth	4.0 m
Line Color Palette	1
Filter	ON
Gain Level	3
Soil Cal	Dry Soil (110)



# GPR system accessories

A comprehensive range of accessories complement the RD1100 and RD1500, broadening their application range, and to provide extra protection during transport.

The products' modular designs also allow for replacement of a number of the key component parts without requiring specialist tools.

#### Wheel sets

Large Wheel Set for GPR Carts Part No: 10/GPRLGWHEELS



Set of 4 wheels for GPR Part No: 10/GPRWHEELSET

1 x GPR wheel

Part No: 10/GPRWHEEL

### **Transport options**

Hard case for GPR display Part No: 10/GPRDISPLAYCASE



Soft case for GPR display unit Part No: 10/GPRDISPBAG

Flight case for GPR system Part No: 10/GPRFLIGHTCASE

#### Software

RD1500 Enhancement Upgrade Part No: 10/RD1500EUPGRADE



RD1500 Utility Suite Analysis

Software

Part No: 10/UTILITY SUITE

### Replacement parts

RD1100 sensor assembly Part No: 10/RD1100SENSOR

Part No: 10/RD1500SENSOR






Replacement sensor skid pad Part No: 10/GPRSKIDPAD

RD1100 display unit

Part No: 10/RD1100DISPLAY





Part No: 10/RD1500DISPLAY



Display mount assembly Part No: 10/GPRMOUNT

RD1100 GPR cart handle Part No: 10/RD1100HANDLE



RD1500 GPR cart handle Part No: 10/RD1500HANDLE

GPR lower cart assembly (no wheels)

Part No: 10/GPRCART



GPR replacement battery pack Part No: 10/GPRBATTERY

Battery Charger - 100V-240V for global use

Part No: 10/GPRCHARGE



Mains leads for battery charger

Part numbers:


US / CAN type: 04/MC-1020 European type: 04/MC-3020 UK type: 04/MC-5020

Australia type: 17/GP3071-C13-25-BK-10A-I



GPR Battery cable

Part No: 10/GPRBATTCABLE



GPR Odometer Assy and Cable Part No: 10/GPRODOMETER

Battery Strap

Part No: 10/GPRBATTSTRAP



GPR 13" Sensor support strap Part No: 10/GPRSTRAP

GPR Handle Pin x 2 Part No: 10/GPRPIN

RD1500 GPS Package Part No. 10/RD1500GPSPACKAGE



































3D data exported using Utility Suite




## FrequenSee<sup>™</sup>


Allows the user to select the low, medium or high part of the frequency spectrum giving the benefits of multiple antennas while maintaining the quality of a single antenna system.

FrequenSee exploits the wide bandwidth of the RD1500 antenna, selectively enhancing shallow and small, medium depth and size, or deep and large targets. Or all at once!









**第三人称形式** 

All



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.

UK Office Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.