










































PROFIBUS connector types overview



We connect your periphery, professional and compact.

Connection type	Cable type	Direction	Product Image	without PG connector	with PG connector
Screw terminals		90°		700-972-0BA12  US	700-972-0BB12  US
		90° with Diagnostic		700-972-7BA12  US	700-972-7BB12  US
		35°		700-972-0BA41  US	700-972-0BB41  US
		axial		700-972-0CA12  US	
		90° with ATEX accreditation		700-973-0BA12  US	700-973-0BB12  US
EasyConnect®	solid	90°		700-972-0BA50  US	700-972-0BB50  US
		90° with Diagnostic		700-972-7BA50  US	700-972-7BB50  US
		angled		700-972-0BA51  US	700-972-0BB51  US
		angled with Diagnostic		700-972-7BA51	700-972-7BB51
		axial		700-972-0CA50  US	
	flexible	90°		700-972-0FA50  US	700-972-0FB50  US
		90° with Diagnostic		700-972-7FA50  US	700-972-7FB50  US
		angled		700-972-0FA51  US	700-972-0FB51  US
		axial		700-972-0CF50  US	
		M12		90°	
90° with Diagnostic				700-974-7BA12	700-974-7BB12
Spring type terminal		90°			700-982-0BB22  US