

**Drive Screws**

**Round Head U-Drive Screws**

A thread forming drive screw with multiple start threads of high helix angle for driving or hammering into metals or plastics.



Head - Round										
Length	Zinc									
	#0	#00	#2	#4	#6	#7	#8	#10	#12	#14
1/8"	32201	32198	32211	32221	32209	-	32217	-	-	-
3/16"	32202	32199	32212	32222	32227	-	32217	-	-	-
1/4"	32203	32200	32213	32223	32228	32233	32218	32238	-	-
5/16"	32206	32207	32216	32225	32210	32236	-	-	-	-
3/8"	32204	32208	32214	32224	32229	32234	32242	32239	32257	-
1/2"	32205	-	32215	32226	32230	32235	32247	32240	32261	32266
5/8"	-	-	-	32220	32231	-	32252	32237	32262	32267
3/4"	-	-	-	-	32232	-	-	-	32263	32268
1"	-	-	-	-	-	-	-	-	0143348	-

**Thumb Screws**

**Thumb Screws**

Tighten and loosen with finger pressure-ideal where frequent disassembly occurs. All screws are fully threaded. Length is measured from under the head.



Head - Spade							
Length	Zinc						
	#6	#8	#10	#12	1/4"	5/16"	3/8"
3/8"	0148458	32751	32759	32768	32776	-	-
1/2"	0148459	32752	32760	32769	32777	32786	-
5/8"	-	32753	32761	32770	32778	-	-
3/4"	0148460	32754	32762	32771	32779	32787	32794
1"	0148461	32755	32763	32772	32780	32788	32795
1-1/4"	-	-	32764	32773	32781	32789	32796
1-1/2"	-	-	32765	32774	32782	32790	32797
2"	-	-	32766	0148462	32783	32791	32798
2-1/2"	-	-	-	-	32784	32792	32775
3"	-	-	-	-	32785	32793	32767

Head - Spade with Shoulder							
Length	Zinc						
	#6	#8	#10	#12	1/4"	5/16"	3/8"
3/8"	0148464	0148467	0148470	-	0148478	-	-
1/2"	-	0148468	0148471	0148475	0148479	0148488	-
5/8"	-	-	-	-	0148480	-	-
3/4"	0148465	-	0148472	0148476	0148481	0148489	0148495
1"	0148466	0148469	0148473	0148477	0148482	0148490	0148496
1-1/4"	-	-	-	-	0148483	0148491	0148497
1-1/2"	-	-	0148474	-	0148484	0148492	0148498
2"	-	-	-	-	0148485	0148493	0148499
2-1/2"	-	-	-	-	0148486	0148494	-
3"	-	-	-	-	0148487	-	0148500

**Wing Screws**

**Stamped Wing Screws**

Wing-like projections from the head of the screw, make it ideal for thumb and forefinger leverage in turning. Ensures rapid assembly and disassembly using only your hand.



- Type D Stamped Steel Zinc Plated.

Coarse					
Length	Zinc				
	#8	#10	1/4"	5/16"	#10
1/4"	0147999	0148003	-	-	0148008
5/16"	0148000	-	-	-	-
3/8"	0148001	-	0148013	-	-
1/2"	0148002	0148004	0148014	0148020	0148009
5/8"	-	0148005	0148015	-	0148010
3/4"	-	0148006	0148016	0148021	0148011
1"	-	0148007	0148017	0148022	0148012
1-1/2"	-	-	0148018	-	-
2"	-	-	0148019	-	-

**Malleable Wing Screws**



Type - Wing Screw									
Length	Zinc								
	#10	1/4"	5/16"	3/8"	1/2"				
1/2"	-	11121985	-	11121997	-	-	-	-	-
5/8"	-	-	-	11121999	11121998	-	-	-	-
3/4"	-	11121989	11121986	11122001	11122000	11122012	11122011	-	11122020
1"	11121981	-	11121990	11122003	11122002	11122013	-	11122024	11122022
1-1/4"	-	-	-	-	11122005	-	11122014	-	-
1-1/2"	-	-	-	11122006	-	11122016	11122015	11122026	11122025
2"	-	11121993	11121995	11122007	-	11122018	-	-	11122029
2-1/2"	-	-	-	11122008	-	-	-	-	-

**Jack Screws**

**Hex Jack Screw Assemblies**

Each assembly comes with (2) #4 Flat Washers, (1) #4 Lock Washer, (1) #4-40 Nut  
Wrench Size is 3/16"



Head - Hex	
Thread Length	Part No.
3/16"	0166953
1/4"	0166954
5/16"	0166955
3/8"	0166956
7/16"	0166957
5/8"	0166958

**Screws**

**Hurricane Shutter Screws**

Low Profile Permanent Anchors for quick and secure shutter installations.



Part No.	Diameter	Thread Size	Material	Point Type
0132040	1/4"	20	Steel	Gimlet
0132043	1/4"	20	Steel	Gimlet

**Accordion Screws**

Stainless steel screws with a 1000 hour coating, specifically designed for the fastening of hurricane shutters.



Diameter	Length	Wrench Size	Stainless Steel Part No.
#10	2"	1/4"	-
#10	3"	1/4"	-
1/4"	1-3/4"	1/4"	-
1/4"	2-3/4"	1/4"	11106688
1/4"	3"	1/4"	-
1/4"	3"	5/16"	-
1/4"	3"	3/8"	-



*Fastenal can re-certify your hoists and pullers in compliance with OSHA regulations.*